

## 95% Minimum Remaining Wall Means Longer Drill Pipe Life

Drill Pipe Size Label 1 (in)	Nominal Weight Label 2 (lb/ft)	API Nominal Wall New (mm)	API		API Minimum Wall Premium Class 80% (mm)	Wall Wear to Premium Class	
			Minimum Wall New 87.5% (mm)	Minimum Wall New 95% (mm)		API Drill Pipe (mm)	TSC Drill Pipe <i>Twice the "Wear-Life"</i> (mm)
2-7/8	10.40	9,19	8,05	8,74 + 0,69	7,36	0,69	1,38
3-1/2	13.30	9,35	8,18	8,88 + 0,70	7,48	0,70	1,40
	15.50	11,40	9,98	10,83 + 0,86	9,12	0,86	1,71
4	14.00	8,38	7,33	7,96 + 0,63	6,71	0,63	1,26
	15.70	9,65	8,45	9,17 + 0,72	7,72	0,72	1,45
4-1/2	16.60	8,56	7,49	8,13 + 0,64	6,85	0,64	1,28
	20.00	10,92	9,56	10,38 + 0,82	8,74	0,82	1,64
	22.82	12,70	11,11	12,07 + 0,95	10,16	0,95	1,91
5	19.50	9,19	8,05	8,74 + 0,69	7,36	0,69	1,38
	25.60	12,70	11,11	12,07 + 0,95	10,16	0,95	1,91
5-1/2	21.90	9,17	8,02	8,71 + 0,69	7,34	0,69	1,38
	24.70	10,54	9,22	10,01 + 0,79	8,43	0,79	1,58
6-5/8	25.20	8,38	7,33	7,96 + 0,63	6,71	0,63	1,26
	27.70	9,19	8,05	8,74 + 0,69	7,36	0,69	1,38